








[illegible]

C-2	REMOVE ALL EXISTING WINDOWS. SEE WINDOW SCHEDULE ON SHEET A-406 FOR NEW REPLACEMENT WINDOW.	C-2A	REMOVE EXISTING METAL LOUVERS TO CRAWL SPACE AND FILL OPENINGS WITH BRICK MASONRY.
C-2	REMOVE EXISTING STEEL LINTEL AND REPLACE WITH NEW PER LOOSE LINTEL SCHEDULE. SEE STRUCTURAL DRAWINGS.	C-2A	REMOVE THE EXISTING GUARDRAIL AND THE TOP OF THE EXISTING CONCRETE WALL TO 1'-0" BELOW GRADE.
C-2A	REMOVE EXISTING THRU-WALL F.A. LOUVER. FILL IN OPENINGS WITH 10" CMU. PROVIDE NEW 30" x 36" GALV METAL LATH AND 3/4" STUCCO EXTERIOR FINISH. SEE FIN SCHEDULE FOR INTERIOR FINISH.	C-2B	PROVIDE AND INSTALL NEW GALVANIZED STEEL LINTELS (SEE LINTEL SCHEDULE ON DWG 3302) TO REPLACE EXISTING LINTELS, & PROVIDE NEW FABRIC FLASHING AT THESE WINDOW HEADS.
C-4	REMOVE EXISTING DOOR AND REPLACE WITH NEW. SEE DOOR SCHEDULE.	C-2A	NEW BRICK JACK ARCHES TO MATCH EXISTING BUILDINGS STANDARD.
C-5	REMOVE ALL EXISTING LIGHT FIXTURES AND REPLACE WITH NEW. SEE ELECTRICAL DWGS.	C-2B	SCRAPE, STEEL BRUSH, PRIME AND FINISH COAT ALL EXISTING STEEL LINTELS NOT BEING REPLACED - TYP.
C-6	ALL EXISTING EXTERIOR STUCCO SURFACES TO BE REFINISHED - SEE SPECIFICATIONS.	C-2B	REPLACE EXISTING LOADING DOCK BUMPERS WITH NEW BUMPERS.
C-6-1	ALL EXISTING FACE BRICK TO BE CLEANED WITH LOW PRESSURE POWER WASHING. SEE SPECIFICATIONS.	C-2B	REMOVE EXISTING HOSE BIB AND RELATED PIPING BACK TO MAIN.
C-6-1	ALL EXISTING FACE BRICK TO BE REPOINTED. SEE SPECIFICATIONS.	C-2B	NEW BRICK VENEER TO MATCH EXISTING TOOTH NEW BRICK INTO EXISTING.
C-6-1	REMOVE EXISTING DAMAGED FACE BRICK. PROVIDE BRICK TO MATCH THE REMAINING EXISTING BRICK. IN SIZE, COLOR AND TEXTURE.	C-2A	NEW ALUMINUM SCREEN W/ HORIZONTAL SLATS TO CONCEAL NEW COOLING TOWERS. SEE DET. 31A-301, STRUT, DWGS, AND MECH. DWGS.
C-10	EXISTING HOOD CORNICE AND GABLE ENDS TO BE SANDED, PRIMED AND PAINTED. SEE SPECIFICATIONS.	C-3B	REMOVE EXISTING STEEL PIPE GUARDRAIL/FENCING COMPLETE. PATCH BRICK WALL AS REQ'D.
C-10	EXISTING WOOD TRIM, CORNICE AND GABLE END OF DORMERS TO BE SCRAPED, REPRIME AND PAINTED. SEE SPECIFICATIONS.	C-3B	EXISTING RAILING TO BE REMOVED COMPLETE. INSTALL NEW GUARDRAIL - REFER TO D-401 FOR SIMILAR DETAIL. UTILIZE EXISTING SLEEVES IN TOP OF CONC. WALL.
C-12	EXISTING FLEXIBLE SEALANT AT CONTROL JOINTS TO BE REPLACED WITH NEW. SEE SPECIFICATIONS.		
C-13	REMOVE EXISTING HANDRAILS AND REPLACE WITH NEW ON EACH SIDE OF STAIR PER DETAIL F-A601.		
C-14	EXISTING WOOD CORNICE TO BE SCRAPED, PRIMED AND PAINTED. SEE SPECIFICATIONS.		
C-15	REMOVE EXISTING BLUESTONE LANDING STAIRS AND RAILINGS. SEE DRAWING A-601 FOR NEW RAMPS AND STAIR AND HANDRAILS.		
C-16	EXISTING WOOD TRIM TO BE SANDED, PRIMED AND PAINTED. SEE SPECIFICATIONS.		
C-17	REMOVE EXISTING PARAPET AND BRICK VENEER BOLD TO EXISTENT BROWN. SEE ELEVATIONS AND WALL SECTION ON DWG A-502 FOR NEW REPLACEMENT CONSTRUCTION. SALVAGE ALL EXISTING BRICK FOR RE-USE IN AREAS TO BE PATCHED.		
C-18	REMOVE EXISTING GLASS BLOCK, STEEL WINDOW AND SUBFRAME. SEE WINDOW SCHEDULE ON SHEET A-406 FOR NEW REPLACEMENT WINDOWS.		
C-19	REMOVE EXISTING LOUVER. INFILL OPENINGS WITH CONSTRUCTION TO MATCH EXISTING SUBGRADE/ EXTERIOR AND INTERIOR SURFACES. SEE MECHANICAL DWGS.		
C-22	REMOVE EXISTING SIGNAGE. SEE SPECIFICATIONS FOR NEW SIGNAGE.		





6-1 REMOVE ALL EXISTING WINDOWS. SEE WINDOW SCHEDULE ON SHEET A-606 FOR NEW REPLACEMENT WINDOWS.

6-2 REMOVE EXISTING STEEL LINTEL AND REPLACE WITH NEW PORE LOOSE LINTEL. SCHEDULE. SEE STRUCTURAL DRAWINGS.

6-3 REMOVE EXISTING THRU-WALL FLA LOUVER. FILL IN OPENING WITH 10" CMU. PROVIDE 1/2" DIA. 1/4" METAL LATH AND 3/4" STICCO EXTERIOR FINISH. SEE FIN SCHEDULE FOR INTERIOR FINISH.

6-4 REMOVE EXISTING DOOR AND REPLACE WITH NEW. SEE DOOR SCHEDULE.

6-5 REMOVE ALL EXISTING LIGHT FIXTURES AND REPLACE WITH NEW. SEE ELECTRICAL DWGS.

6-6 ALL EXISTING EXTERIOR STICCO SURFACES TO BE REFINISHED - SEE SPECIFICATIONS.

6-7 ALL EXISTING FACE BRICK TO BE CLEANED WITH HIGH PRESSURE POWER WASHER. SEE SPECIFICATIONS.

6-8 ALL EXISTING FACE BRICK TO BE REPOINTED. SEE SPECIFICATIONS.

6-9 REMOVE EXISTING DAMAGED FACE BRICK. PROVIDE BRICK TO MATCH THE REMAINING EXISTING BRICK IN SIZE, COLOR AND TEXTURE.

6-10 EXISTING MOOD CORNICE AND GABLE ENDS TO BE SANDED, PRIMED AND PAINTED. SEE SPECIFICATIONS.

6-11 EXISTING MOOD TRIM, CORNICE AND GABLE END OF DORMERS TO BE SCRAPED, PRIMED AND PAINTED. SEE SPECIFICATIONS.

6-12 EXISTING FLEXIBLE SEALANT AT CONTROL JOINTS TO BE REPLACED WITH NEW. SEE SPECIFICATIONS.

6-13 REMOVE EXISTING HANDRAILS AND REPLACE WITH NEW ON EACH SIDE OF STAIR PER DETAIL A-601.

6-14 EXISTING MOOD CORNICE TO BE SCRAPED, PRIMED AND PAINTED. SEE SPECIFICATIONS.

6-15 REMOVE EXISTING BLUESTONE LANDING, STAIRS AND RAILINGS. SEE DRAWING A-601 FOR NEW RAMPS AND STAIR AND HANDRAILS.


6-16 EXISTING MOOD TRIM TO BE SANDED, PRIMED AND PAINTED. SEE SPECIFICATIONS.

6-17 EXISTING PARAPET AND BRICK VENEER BELOW TO EXTENT SHOWN. SEE ELEVATIONS AND WALL SECTION ON DWG A-502 FOR NEW REPLACEMENT CONSTRUCTION. SALVAGE ALL EXISTING BRICK FOR RE-USE IN AREAS TO BE PATCHED.

6-18 EXISTING EXISTING GLASS BLOCK, STEEL WINDOW AND SUBFRAME. SEE WINDOW SCHEDULE ON SHEET A-606 FOR NEW REPLACEMENT WINDOWS.


6-19 REMOVE EXISTING LOUVER. INFILL OPENINGS WITH CONSTRUCTION TO MATCH EXISTING SURROUNDING EXTERIOR AND INTERIOR SURFACES. SEE MECHANICAL DWGS.

6-20 REMOVE EXISTING SIGNAGE. SEE SPECIFICATIONS FOR NEW SIGNAGE.



ADDRESS:
4021 Main Street
Stratford, Connecticut 06614
Tel: 203-377-1300
Fax: 203-378-3002
Email: architects@antinozzi.com

COPYRIGHT 2000 BY:
ANTINOZZI ASSOCIATES, P.C.
These documents have been prepared
specifically for this project.
Reproduction or other use of these
documents is prohibited without the
approval of the Architect or Engineer.




DATE	DESCRIPTION
09-14-00	ISSUED FOR PRELIMINARY BUDGET
10-27-00	ISSUED FOR BIDDING
03-01-01	ISSUED FOR REVIEW
04-02-01	ISSUED FOR PRE-BID REVIEW
04-16-01	ISSUED FOR BIDS

STATE PROJECT NO: 158-091A/R
CONVERSION OF BEDFORD MIDDLE SCHOOL
TO THE SAUGATUCK ELEMENTARY SCHOOL
170 RIVERSIDE AVENUE
WESTPORT, CONNECTICUT

EXTERIOR ELEVATIONS


SCALE:	DRAWN BY:
1/8" = 1'-0"	PAL
DRAWING NO:	
A-303	
DATE:	JOB NUMBER:
11-9-2000	00087




7 EAST
EXTERIOR ELEVATION - COURTYARD
1/8"=1'-0"




8 SOUTH
EXTERIOR ELEVATION - COURTYARD
1/8"=1'-0"




9 WEST
EXTERIOR ELEVATION - COURTYARD
1/8"=1'-0"




10 NORTH
EXTERIOR ELEVATION - COURTYARD
1/8"=1'-0"



11 EXTERIOR ELEVATION - EAST
1/8"=1'-0"




A WALL SECTION - LOADING DOCK
SCALE: 3/4" = 1'-0"




B WALL SECTION @ STAIR #5
SCALE: 3/4" = 1'-0"

ELEVATION DEMOLITION AND CONSTRUCTION NOTES


- (C-1) REMOVE ALL EXISTING WINDOWS. SEE WINDOW SCHEDULE ON SHEET A-406 FOR NEW REPLACEMENT WINDOWS.
- (C-2) REMOVE EXISTING STEEL LINTEL AND REPLACE WITH NEW PER LOOSE LINTEL SCHEDULE. SEE STRUCTURAL DRAWINGS.
- (C-3) REMOVE EXISTING THRU-WALL F.A. LOUVER. FILL IN OPENING WITH 10" CMU. PROVIDE NEW 3/8" THK GALV METAL LATH AND 5/4" STUCCO EXTERIOR FINISH. SEE FIN SCHEDULE FOR INTERIOR FINISH.
- (C-4) REMOVE EXISTING DOOR AND REPLACE WITH NEW. SEE DOOR SCHEDULE.
- (C-5) REMOVE ALL EXISTING LIGHT FIXTURES AND REPLACE WITH NEW. SEE ELECTRICAL DWGS.
- (C-6) ALL EXISTING EXTERIOR STUCCO SURFACES TO BE REFINISHED - SEE SPECIFICATIONS.
- (C-7) ALL EXISTING FACE BRICK TO BE CLEANED WITH LOW PRESSURE POWER WASHING. SEE SPECIFICATIONS.
- (C-8) ALL EXISTING FACE BRICK TO BE REPOINTED. SEE SPECIFICATIONS.
- (C-9) REMOVE EXISTING DAMAGED FACE BRICK. PROVIDE BRICK TO MATCH THE REMAINING EXISTING BRICK IN SIZE, COLOR AND TEXTURE.
- (C-10) EXISTING WOOD CORNICE AND GABLE ENDS TO BE SANDED, PRIMED AND PAINTED. SEE SPECIFICATIONS.
- (C-11) EXISTING WOOD TRIM, CORNICE AND GABLE END OF DORMERS TO BE SANDED, PRIMED AND PAINTED. SEE SPECIFICATIONS.
- (C-12) EXISTING FLEXIBLE SEALANT AT CONTROL JOINTS TO BE REPLACED WITH NEW. SEE SPECIFICATIONS.
- (C-13) REMOVE EXISTING HANDRAILS AND REPLACE WITH NEW ON EACH SIDE OF STAIR PER DETAIL A-601.
- (C-14) EXISTING WOOD CORNICE TO BE SANDED, PRIMED AND PAINTED. SEE SPECIFICATIONS.
- (C-15) REMOVE EXISTING BLUESTONE LANDING, STAIRS AND RAILINGS. SEE DRAWING A-601 FOR NEW RAMP AND STAIR HANDRAILS.
- (C-16) EXISTING WOOD TRIM TO BE SANDED, PRIMED AND PAINTED. SEE SPECIFICATIONS.
- (C-17) REMOVE EXISTING PARAPET AND BRICK VENEER BELOW TO EXIST SHOWN. SEE ELEVATIONS AND WALL SECTION ON DWG A-502 FOR NEW REPLACEMENT CONSTRUCTION. SALVAGE ALL EXISTING BRICK FOR RE-USE IN AREAS TO BE PATCHED.
- (C-18) REMOVE EXISTING GLASS BLOCK, STEEL WINDOW, AND SUBFRAME. SEE WINDOW SCHEDULE ON SHEET A-406 FOR NEW REPLACEMENT WINDOWS.
- (C-19) REMOVE EXISTING LOUVER. FILL IN OPENING WITH CONSTRUCTION TO MATCH EXISTING SURROUNDING EXTERIOR AND INTERIOR SURFACES. SEE MECHANICAL DWGS.
- (C-20) REMOVE EXISTING SIGNAGE. SEE SPECIFICATIONS FOR NEW SIGNAGE.
- (C-21) REMOVE EXISTING METAL LOUVERS TO GRAVEL SPACE AND FILL OPENING WITH BRICK MASONRY.
- (C-22) REMOVE THE EXISTING GUARDRAIL AND THE TOP OF THE EXISTING CONCRETE WALL TO 1'-0" BELOW GRADE.
- (C-23) PROVIDE AND INSTALL NEW GALVANIZED STEEL LINTELS (SEE LINTEL SCHEDULE ON DWG S202) TO REPLACE EXISTING LINTELS, & PROVIDE NEW FABRIC FLASHING AT THESE WINDOW HEADS.
- (C-24) NEW BRICK JACK ARCHES TO MATCH EXISTING BUILDING STANDARD.
- (C-25) SCRAPE, STEEL BRUSH, PRIME AND FINISH COAT ALL EXISTING STEEL LINTELS NOT BEING REPLACED - TYP.
- (C-26) REPLACE EXISTING LOADING DOCK BUMPERS NEW NEW BUMPERS.
- (C-27) REMOVE EXISTING HOSE BIB AND RELATED PIPING BACK TO MAIN.
- (C-28) NEW BRICK VENEER TO MATCH EXISTING. TOOTH NEW BRICK INTO EXISTING.
- (C-29) NEW ALUMINUM SCREEN W/ HORIZONTAL SLATS TO CONCEAL NEW COOLING TOWERS. SEE DET. 3/A-501, STRUCT. DWGS, AND MECH. DWGS.
- (C-30) REMOVE EXISTING STEEL PIPE GUARDRAIL/FENCING COMPLETE. PATCH BRICK WALL AS REQ'D.
- (C-31) EXISTING RAILING TO BE REMOVED COMPLETE. INSTALL NEW GUARDRAIL - REFER TO D-4001 FOR SIMILAR DETAIL. UTILIZE EXISTING SLEEVES IN TOP OF CONC. WALL.




15 EXTERIOR ELEVATION - PARTIAL WEST
1/8"=1'-0"



C WALL SECTION - LOADING DOCK
SCALE: 3/4" = 1'-0"



KEY PLAN
SCALE: 1" = 100'



- 2- REMOVE EXISTING NAIL LOUVERS TO CRANK SPACE AND FILL OPENING WITH BRICK MASONRY.
- 2- REMOVE THE EXISTING GUARDRAIL AND THE TOP OF THE EXISTING CONCRETE HALL TO 1'-0" BELOW GRADE.
- 2- PROVIDE AND INSTALL NEW GALVANIZED STEEL LINTELS (SEE LINTEL SCHEDULE ON DRAWING) TO REPLACE EXISTING LINTELS, 1 PROVIDE NEW FABRIC CURTAIN WALLS AT THESE WINDOW HEADS.
- 2- NEW BRICK JACK ARCHES TO MATCH EXISTING BUILDING STANDARD.
- 2- SCRAPE, STEEL BRUSH, PRIME AND FINISH COAT ALL EXISTING STEEL LINTELS NOT BEING REPLACED - TYP.
- 2- REPLACE EXISTING LOADING DOCK BUMPERS NEW HUB BUMPERS.
- 2- REMOVE EXISTING HOSE BIB AND RELATED PIPING BACK TO MAIN.
- 2- NEW BRICK VENEER TO MATCH EXISTING. TOOTH NEW BRICK INTO EXISTING.
- 2- NEW ALUMINUM SCHEDULE N HORIZONTAL SLATS TO CONCEAL NEW COOLING TOWERS. SEE DET. 3/1A-501, STRUCT. DWGS. AND MECH. DWGS.
- 2- REMOVE EXISTING STEEL PIPE GUARDRAIL/FENCING COMPLETE. PATCH BRICK HALL AS REQ'D.
- 2- EXISTING RAILING TO BE REMOVED COMPLETE. INSTALL NEW GUARDRAIL - REFER TO DRAWING FOR SIMILAR DETAIL. UTILIZE EXISTING SLEEVES IN TOP OF CONC. WALL.